LZ360-USB/WDP Laser Scanner Specifications

Model	Description	Interface	Cable
LZ360-USB	Integrated USB Laser Scanner	USB HID Keyboard	C40 USB Cable
LZ360-WDP	Integrated Keyboard Laser Scanner	Keyboard 6-Pin Mini Din	C41 Keyboard Y-Cable

Operational

|	
Light Source	650 nm Laser Diode
Scan Speed	100 scans/sec Bidirectional
Scan Angle	53º ± 2º
Minimum Bar Width	2.7 mil .0027" (0.069mm)
Print Contrast	20% minimum reflectance differential
Indicators (LED)	Bi-Color LED - Green/Decode Orange/Scan
Beeper Operation	5 Tones plus OFF
System Interface(s)	USB HID Keyboard or Keyboard Wedge
Operating System	Windows® 7, Vista, XP, NT, 2000, 98SE, Mac OS
Bar Codes Supported	Code 39, Full ASCII Code 39, UPC-A, UPC-E, EAN-13, EAN-8, ISBN, Code 93, 2 of 5 Standard, Interleaved 2 of 5, Codabar, Code 128, RSS-14 UCC/EAN 128, MSI, Plessey

Physical

Height	5.6" (142mm)
Depth	4.7"(119mm)
Width	3.1" (79mm)
Weight	8.8 oz - 249g
Cables	C40 USB 6' (1800mm) Straight Cable or C41 Keyboard Wedge 6' (1800mm) Y-Cable

Power

Input Voltage	5VDC ± 10%
Power (nominal)	25mA Idle, 93mA scanning
Laser Class	CDRH class II / IEC class 2
EMC	FCC part 15 class A EN 55024, 61000-3-2, 61000-3-3 CE Compliant

Environmental

|	
Operating Temperature	14ºF to 122ºF (-0ºC to 50ºC)
Storage Temperature	-4ºF to 140ºF (-20ºC to 60ºC)
Humidity	5% to 95% non-condensing
Ambient Light Immunity	Sunlight: 8,000 ft. candles - Indoor: 450 ft. candles
Shock	6' drop to concrete
Warranty	2 Years - Parts & Labor

5.6"

3.1"   1.8"

4.7"

C41 6 pin mini-din PC Keyboard Y Cable

CAUTION
LASER LIGHT WHEN OPEN
DO NOT STARE INTO BEAM
CLASS II LASER PRODUCT
IEC CLASS 2 LASER PRODUCT
680 nm LASER • 1.0 MILLIWATT MAX OUTPUT
COMPLIES WITH US DHHS 21 CFR 1040. @ SUBCHAPTER J AND IEC 825-1 1993/EN60825. ACHTUNG LASERSTRAHL, LASERKLASSE 2, NICHT IN DEN STRAHL BLICKEN. LUMIERE LASER - NE PAS REGARDER DANS LE FAISCEAU APPAREIL A LASER DE CLASSE 2
WORTH DATA INC. • SANTA CRUZ, CA.

C40 USB Cable for PC or Mac

Scan Range for LZ360-USB & LZ360-WDP

0"   10"   20"   30"   40"

6"
10"
2"   36" 41"   48 "

●6 mil narrow bar width   ●10 mil narrow bar width   ●40 mil narrow bar width   ●100 mil narrow bar width, retro-reflective media

CE

USB

FC

MADE IN USA
OF USA AND IMPORTED PARTS